

**Thermo Scientific
Multiskan FC
Microplate
Photometer**



**Filter-based microplate photometer for
research and routine applications**

Thermo Scientific Multiskan FC – Filter-based Microplate Photometer for Research and Routine Applications

The Thermo Scientific Multiskan FC microplate photometer is a reliable and robust instrument for a wide variety of research and routine applications. It reads both 96- and 384- well plates, and is equipped with shaking as well as incubation capabilities for temperature critical assays. It can be used as a stand-alone instrument or under PC-control with our intuitive Thermo Scientific Skanlt Software.

Designed with 30 years experience in microplate photometry, the Multiskan® FC combines the world renowned quality of the Multiskan product line with a new large color screen, visual internal software with 'quick keys' and multiple language options to ensure excellent usability.

Multiskan FC Offers You

- A broad wavelength range of 340 - 850 nm for a wide variety of research and routine applications
- Fast and accurate measurement of both 96- and 384-well plates for varying throughput requirements
- Shaking and incubation up to 50°C for temperature critical assays
- Ease of use through the large color screen, visual internal software and a variety of language versions
- Visual and logical Skanlt Software for comprehensive instrument control and data handling
- Proven performance and reliable day-to-day results through patented optical design and in-built self diagnostics
- Designed with 30 years experience in microplate photometry

Multiskan FC for a Wide Variety of Photometric Applications

Multiskan FC is a reliable and robust microplate photometer designed to perform a wide variety of routine and research applications. It brings together 30 years experience of the well known Multiskan product brand, with new features for enhanced usability. The Multiskan FC can be used as a stand-alone instrument or under PC control via our unique and easy-to-use Skanlt Software.


The Multiskan FC boasts a 340 – 850 nm wavelength range, enabling a wide variety of applications from enzyme kinetic studies through to Lowry assays. It is equipped with an eight position filter wheel with three standard filters 405, 450 and 620 nm pre-installed. A comprehensive range of easy to install additional filters is available to order directly from your Thermo Fisher Scientific representative.

The Multiskan FC offers fast and accurate measurements providing complete 96-well plate reading in less than 6 seconds. Furthermore, the instrument is equipped with linear shaking as standard. Moreover, a model is available fitted with an incubator providing incubation temperatures up to 50° C and the capacity to read 384-well plates.

Reliable Results and Robust Performance

The proven and patented (US6111636) optical design of the Multiskan FC in combination with the auto-calibration procedure that is performed during each measurement, guarantees stable day-to-day and year-on-year performance and reliability.

During start up all major functions of the instrument, such as plate position, measurement stability, lamp functionality, filters, optical system, incubation and electronic operation, are checked to ensure reliable operation. Additionally, the



Patented and proven optical design (US6111636)



lamp is automatically switched off when not in use, thus prolonging the lifetime of the lamp.

Ease of Use with Internal Software

The large color screen of the Multiskan FC combined with the simple and logical internal software ensures easy and intuitive assay setup. The 'quick keys' allow instant access to the most commonly used protocols in routine laboratories. In addition, the internal software contains both qualitative and quantitative calculations for single, dual and kinetic measurements offering flexible data handling capabilities. The internal software memory can store up to 99 assays, and results can be saved to a USB memory stick for easy transfer to a computer.

The internal software is available in English, German, French, Spanish, Portuguese, Russian, Chinese, and Japanese.

Thermo Scientific SkanIt Software for Optimal Computer Control

The highly visual and logical user interface of the SkanIt® Software, makes instrument control and data handling for both research and routine applications easy. The graphical step list feature allows straightforward setup of any assay. Comprehensive inbuilt calculations, such as: blank subtraction; quantitative curve fit; qualitative classification and kinetic calculations, as well as the versatile reporting tool, make data reduction with SkanIt Software trouble-free. Using the ready-made demo sessions in

the SkanIt Software, basic single, dual- and kinetic measurements are performed quickly with only a few mouse clicks. Furthermore, ready-made sessions for many common assays can be downloaded for the SkanIt Software online from the Reading Room (www.thermo.com/readingroom).

Robot Compatibility for High Throughput Environments


The plate carrier on the Multiskan FC is specially designed for convenient stacker and robot arm access, allowing microplate gripping in both portrait and landscape configurations. Additionally, the SkanIt Software automation interface enables easy integration with robotic software.

Multiskan Verification Plate for Instrument Verification

The Multiskan Verification Plate combined with the SkanIt Software verification feature, offers an excellent tool for verifying instrument performance and allows users to prove the integrity and validity of their results. Additionally, the installation, operation and performance qualification (IQ/OQ/PQ) package provides a convenient way to document evidence demonstrating the integrity of the instrument and its performance.

Meets RoHS Directive

Built using the highest quality components, Multiskan FC conforms to the RoHS (Restriction of Hazardous Substances) directives.



Visual and logical user interface of SkanIt Software



Large color screen and visual internal software

Applications: Immunoassays (ELISA), protein assays, endotoxins, cytotoxicity and proliferation assays, enzyme assays, growth curves

USB port for easy data transfer.



Robot-friendly plate carrier for both 96- and 384-well plates



Technical Specifications	
Light source	Quartz-halogen lamp 6 V / 10 W
Wavelength range	340 – 850 nm
Filters	8-position filter wheel, the instrument is delivered with the following standard filters installed: 405 nm; 450 nm; and 620 nm. Additional filters can be ordered separately.
Half-bandwidth of filters	3 – 9 nm
Read-out range	0 – 6 Abs
Linearity (405 nm)	0 – 3 Abs, ± 2%, 96-well plate, fast mode 0 – 4 Abs, ± 2%, 96-well plate, normal mode 0 – 2.5 Abs, ± 2%, 384-well plate, fast mode 0 – 3 Abs, ± 2%, 384-well plate, normal mode
Resolution	0.001 Abs
Accuracy (405 nm)	± 1% (0.3 – 3 Abs), ± 2% (3 – 4 Abs)
Precision (405 nm)	CV ≤ 0.2% (0.3 – 3 Abs), CV ≤ 1.0% (3 – 4 Abs)
Measurement speed	6 s, 96-well plate, fast mode 12 s, 96-well plate, normal mode 11 s, 384-well plate, fast mode 33 s, 384-well plate, normal mode
Optional incubator	Temperature range from ambient + 4° C up to 50° C
Shaking	Linear shaking with three modes: slow, medium and fast
Robotic compatibility	Yes
Display	High contrast color display (480 x 272 dots)
User interface	Internal software or PC control with SkanIt Software
Internal memory (standalone)	At least up to 99 assay protocols and 100 test results, 96-well plate
External printer type	HP PCL5
Communication	USB for computer connection USB memory stick position for data export USB for external printer
Mains input	100 – 240 V (50/60 Hz)
Power consumption	Max. 100 VA, standby 8 VA
Overall dimensions (H x W x D)	210 x 290 x 400 mm 8.3 x 11.4 x 15.7 in.
Weight	8.5 kg (18.7 lbs.)
Conformity to regulations	2006/95/EC (Low Voltage Directive) 2004/108/EC (Electromagnetic Compatibility Directive, EMC) FCC Part 15, Subpart B/Class B (July 2004) 2002/96/EC (Waste of Electrical and Electronic Equipment)
PC requirements for SkanIt Software	
Minimum system requirements	IBM® PC compatible computer with Intel Pentium 4. 1 GB RAM, 5 GB free hard disk space, USB, CD-ROM drive, mouse or equivalent, XVGA monitor with 1024 x 768 resolution
Operating system	Microsoft Windows® XP Professional with service pack 2 or Microsoft Windows Vista® 32 or 64 bit Business edition

Ordering information					
Code	Instrument	Shaking	Incubation	96-well plates	384-well plates
51119000	Multiskan FC	X		X	
51119100	Multiskan FC with incubator	X	X	X	X

© 2009 Thermo Fisher Scientific Inc. All rights reserved. Windows and Vista are registered trademarks of Microsoft Corporation. IBM is a registered trademark of International Business Machines Corporation. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

North America: USA/Canada 1 800 522 7763

Europe: Austria +43 1 801 40 0, Belgium +32 2 482 30 30, France +33 2 2803 2180, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 02 95059 448, Netherlands +31 76 571 4440, Nordic/Baltic countries +358 9 329 100, Russia/CIS +7 (495) 739 76 41, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203

Asia: China +86 21 6865 4588 or +86 10 8419 3588, India toll free 1800 22 8374 India +91 22 6716 2200, Japan +81 45 453 9220,

Other Asian countries +852 2885 4613 **Countries not listed:** +49 6184 90 6940 or +33 2 2803 2180

www.thermo.com/readingroom

www.thermo.com/mpi

Thermo
SCIENTIFIC